



HSIN CHANG CORP.

CONTINUOUS REFINEMENT
CUSTOMER SATISFACTION
QUALITY FIRST

Outstanding technique

to believe in your insights is to believe in professions.

Each product has a remarkable achievement in our company, such as Hollow Wall Anchors, Speed Plugs, Express Nails, Frame Anchors, Nylon Hammer Fixings, and Steel Hammer Anchors...else



Customer Satisfaction

Continuous Refinement

Quality First



欣彰工業股份有限公司
HSIN CHANG HARDWARE INDUSTRIAL CORP.

Add.: No. 58, Ln. 455, Punei St., Changhua City, Changhua County 500, Taiwan

Tel.: +886 (4) 71 35 87 9 Fax: +886 (4) 71 35 86 6

E-Mail: sales@hsinchang.com.tw

Website: www.hsinchang.com.tw



Website



E-mail

Hollow Wall Anchors
Speed Plugs
Express Nails
Frame Anchors
Nylon Hammer Fixings
Steel Hammer Anchors

hsinchang.com.tw

HSIN CHANG GROUP *is your best choice!*



Introduction

Hsin Chang group has been manufacturing and exporting anchors since 1981, our headquarters with the land area of 1,100 square meters located at Changhua, Huatan township in Taiwan. We mainly produce for exporting about anchors and accumulated decades of production and sales experience fruitful, therefore our customers are now around the world. In order to fulfill the marketing demands, we set up a factory with the land area of 30,000 square meters in Shenzhen of China in November 1992, and expansion the second factory next to our headquarters with the land area of 3,000 square meters in April 2005. Respond to Mainland government policy changes and long-term management considerations, we closed the factory in Shenzhen of China in December 2019 and expansion our headquarters with the land area of 7,000 square meters to Changhua city in February 2020, the employees are around 90-120 people and continued increase.

Each product has a remarkable achievement in our company, such as Hollow Wall Anchors, Speed Plugs, Express Nails, Frame Anchors, Nylon Hammer Fixings, and Steel Hammer Anchors...else, production is growing steadily; we have professional R&D design, production and business marketing team from production

to sales, we hold high-quality product and provide the best service to customers, actively develop automated manufacturing in recent years to satisfy market consumption requirement. In addition, we have successfully develop a variety of new products and got the international patents from US, Australia and Europe. We also cooperated with the well know manufactures who are specialized in fastener by OEM/ODM for long term partners, assist customers to get patent and ETA certification together.

For the management, we began an ISO 9002 certified manufacturer on February 17th, 1997. And get ISO 9001 certificate in 2015, we strict controlling the quality and production to offer good quality products for our customers. We bought and used the text equipment, various software and machines to keep our occurrence of defective products maintained less than 0.5 percent.

Hsin Chang purpose is Continuous Refinement, Quality Frst, and Customer Satisfaction, we will continue to provide the most competitive prices in order to provide each and every one of our customers with the most sincerely and perfect service.



Quality Policy

Continuous Refinement
Quality First
Customer Satisfaction

Quality Commitment

ISO 9001
Patent Continuous Development

Quality Target

Continue to introduce automation equipment and update software
Maintain product defect rate below 0.5%

Rate of Sales Area

EUROPE	50%
JAPAN	25%
AMERICA	10%
OTHERS	15%



Monthly Volume of Products

Hollow Wall Anchor	18,000 MPCS
Metal Anchor Series	2,000 MPCS
Nylon Anchor Series	6,000 MPCS
Speed Plug	15,000 MPCS
Others	18,000 MPCS

Production Equipment

Stamping
Heading
Wire-cutting Machine
Die-casting Machine
Plastic Injection Machine

Inspection Equipment

Non-destructive Coating Thickness Tester
Hydraulic Destructive Tensile Strength Tester
Multi-destructive 3-dimension
Salt Spray Tester
Cord Torsion Tester
Hardness Tester



Products Index

Hollow Wall Anchors (M-TYPE)	04
Hollow Wall Anchors (J-TYPE)	05
Hollow Wall Drive Anchors (M-TYPE)	05
Hollow Wall Anchors (One Piece) Self-Drilling	06
Hollow Wall Anchors (One Piece)	06
Anchor Setting Tools	07
Speed Plugs	08
Frame Anchors	09
Saw Steel Plugs	09
Express Nails	09
Nylon Frame Anchors	10
Nylon Hammer Fixings	10
Nylon Fixings	10
H.C.Bolt Anchors	11
Steel Hammer Anchors	12
Key Anchors	12
Toggle Bolts	13
Plastic Anchors	13
Hammer Drive Anchors	14
J-Nuts	14
Steel Expansion Anchors	15
Nylon Expansion Anchors	15
Tie Wire Anchors	16
Purlin Clips	16
Hooks	16
Packing	17



ISO 9001

Outstanding technique

to believe in your insights is to believe in professions.

03





Hollow Wall Anchors

The thickness of steel plate: M4-0.6mm, M5-0.8mm, M6-0.8mm.

Material: Steel

Surface treatment: Zinc Plated CR3+

M TYPE



Item No.:	SPECIFICATION						unit : mm
	Size	Screw	L	A	Drill (Ø)	Grip	
405	4XS	M4	25	21	8	UP-5	
409	4S	M4	39	32	8	5-12	
422	4SL	M4	52	46	8	3-20	
423	4L	M4	52	45	8	18-24	
438	4XL	M4	65	59	8	32-38	
507	6XS	M5	32	25	11	1.6-6.4	
509	6MS	M5	36	30	11	1.6-9.5	
510	6E	M5	44	37	11	6-13	
514	6S	M5	58	52	11	3-16	
527	6L	M5	71	65	11	14-32	
545	6XL	M5	88	80	11	32-45	
610	8E	M6	44	37	13	6-13	
614	8S	M6	58	52	13	3-16	
627	8L	M6	71	65	13	14-32	
645	8XL	M6	88	80	13	32-45	

Item No.:	SPECIFICATION						unit : inch
	Size	Screw	L	A	Drill (Ø)	Grip	
405	1/8"XS	6-32	1"	13/16"	5/16"	UP to 1/4"	
409	1/8"S	6-32	1-1/2"	1-1/4"	5/16"	1/8" to 1/2"	
422	1/8"SL	6-32	2-1/16"	1-13/16"	5/16"	1/8" to 3/4"	
423	1/8"L	6-32	2-1/16"	1-13/16"	5/16"	5/8" to 7/8"	
438	1/8"XL	6-32	2-9/16"	2-5/16"	5/16"	1-1/4" to 1-1/2"	
510	3/16"E	10-24	1-13/16"	1-1/2"	7/16"	1/4" to 1/2"	
514	3/16"S	10-24	2-1/4"	2-1/16"	7/16"	1/8" to 5/8"	
527	3/16"L	10-24	2-3/4"	2-9/16"	7/16"	5/8" to 1-1/4"	
545	3/16"XL	10-24	3-1/2"	3-1/8"	7/16"	1-1/4" to 1-3/4"	
610	1/4"E	1/4-20	1-13/16"	1-1/2"	1/2"	1/4" to 1/2"	
614	1/4"S	1/4-20	2-1/4"	2-1/16"	1/2"	1/8" to 5/8"	
627	1/4"L	1/4-20	2-3/4"	2-9/16"	1/2"	5/8" to 1-1/4"	
645	1/4"XL	1/4-20	3-1/2"	3-1/8"	1/2"	1-1/4" to 1-3/4"	





Hollow Wall Anchors

The thickness of steel plate: M4-0.6mm, M5-0.8mm, M6-0.8mm.

Material: Steel

Surface treatment: Zinc Plated CR3+

J TYPE



Item No.:	SPECIFICATION						unit : mm
	Size	Screw	L	A	Drill (Ø)	Grip	
405	4XS	M4	25	20	9	UP-4	
409	4S	M4	39	32	9	3-11	
412	4E	M4	42	35	9	5-12	
416	4MS	M4	45	38	9	8-16	
423	4L	M4	52	45	9	16-23	
427 (425)	4EL	M4	60	54	9	17-27	
438	4XL	M4	65	60	9	31-38	
514	6S	M5	58	52	11	7-16	
527	6L	M5	71	65	11	17-32	
545	6XL	M5	88	80	11	32-45	
614	8S	M6	58	52	13	7-16	
627	8L	M6	71	65	13	17-32	
645	8XL	M6	88	80	13	32-45	
810	E	M8	45	37	14	6-13	
814	S	M8	58	52	14	3-16	
827	L	M8	71	65	14	17-32	
845	XL	M8	88	80	14	32-45	


Hollow Wall Drive Anchors

The thickness of steel plate: M4-0.6mm.

Material: Steel

Surface treatment: Zinc Plated CR3+

M TYPE



Item No.:	SPECIFICATION						unit : inch
	Size	Screw	L	A	Drill (Ø)	Grip	
405D	1/8"XSD	6-32	1-3/8"	13/16"	5/16"	UP to 1/4"	
409D	1/8"SD	6-32	1-3/4"	1-1/4"	5/16"	1/8" to 1/2"	
422D	1/8"SLD	6-32	2-5/16"	1-13/16"	5/16"	1/8" to 3/4"	
423D	1/8"LD	6-32	2-5/16"	1-13/16"	5/16"	5/8" to 7/8"	





Hollow Wall Anchors (One Piece)

The thickness of steel plate: M4-0.8mm, M5-1.0mm, M6-1.0mm.

Material: Steel
Surface treatment: Zinc Plated CR3+

Self-Drilling No need to drill a hole in advance.





Item No.:	SPECIFICATION						unit : mm
	Size	Screw	L	A	Drill (Ø)	Grip	
409	4S	M4	42	34	7.2	3-11	
412	4E	M4	45	37	7.2	5-12	
416	4MS	M4	49	40	7.2	8-16	
510	5E	M5	47	36	10.8	3-13	
610	6E	M6	47	36	10.8	3-13	



Hollow Wall Anchors (One Piece)

The thickness of steel plate: M4-0.8mm, M5-1.0mm, M6-1.0mm.

Material: Steel
Surface treatment: Zinc Plated CR3+



Item No.:	SPECIFICATION						unit : mm
	Size	Screw	L	A	Drill (Ø)	Grip	
409	4S	M4	40	34	9	3-13	
422	4SL	M4	52	46	9	3-20	
510	5E	M5	44	36	12	3-13	
514	5S	M5	58	50	12	3-16	
545	5XL	M5	83	75	13	16-45	
610	6E	M6	44	36	12	3-13	
614	6S	M6	58	50	12	3-16	
645	6XL	M6	83	75	13	16-45	



Anchor Setting Tools

For Hollow Wall Anchors.



AT-17

- 1.Material: Aluminum Alloy.
 - 2.Surface treatment: Electro-coating.
 - 3.Handle: PVC (color and mark can be customized).
 - 4.For Hollow Wall Anchors M4, M5, M6.
 - 5.Light.
- Read more refer to page 08.



AT-82

- 1.Material: Aluminum Alloy.
- 2.Surface treatment: Painting.
- 3.Handle: PVC (color and mark can be customized).
- 4.For Hollow Wall Anchors M4, M5, M6.
- 5.Easy to use in corners.



AT-88

- 1.Material: Aluminum Alloy.
- 2.Surface treatment: Electro-coating.
- 3.Handle: PVC (color and mark can be customized).
- 4.For Hollow Wall Anchors M4~6 and enlarge for M8.



AT-87

- 1.Material: Steel.
- 2.Surface treatment: Chrome plating.
- 3.Handle: PVC (Color and Mark can be customized).
- 4.For Hollow Wall Anchors M4, M5, M6.



AT-80

- 1.Material: Steel.
- 2.Surface treatment: Black plating.
- 3.For Hollow Wall Anchors M4, M5, M6.



AT-83

- 1.Material: Steel.
- 2.Surface treatment: Chrome plating.
- 3.Handle: PVC coating (color can be customized).
- 4.For Hollow Wall Anchors M4, M5, M6.



AT-85

- 1.Material: Steel.
- 2.Surface treatment: Black plating.
- 3.Handle: PVC (color and mark can be customized).
- 4.For Hollow Wall Anchors M4, M5, M6.



AT-86

- 1.Material: SGCC.



AT-89

- 1.Material: Stainless.

Latest Tool For Hollow Anchors AT-17

Light weight -16%
Labor saving
Accurate

New!

Patented
(Taiwan/Mainland/Germany/France)

The advantages are:


1. Lightweight.
2. Scaled (used to refer to riveting thickness).
3. The center point is most accurate during auxetic expansion. (the expansion foot will not be pulled crookedly)



Zinc Alloy Speed Plugs

Material: Zinc Alloy


SPECIFICATION		unit : mm	
Size	Screw	L	D (Ø)
SP-A	4.5x30	28.5	15
		28	13
SP-G	4.5x35	37	13
SP-H	4.5x35	31	13



Nylon Speed Plugs

Material: Nylon


SPECIFICATION		unit : mm	
Size	Screw	L	D (Ø)
SP-N	4.5x22	33	14.5
SP-Q	4.5x30	37	13
SP-R	4.5x30	28	15



Frame Anchors

Material: Screw - Steel
Nut - Zinc Alloy
Cap - PP

Surface treatment: Screw-Zinc Plated CR3+




SPECIFICATION			unit : mm	
Size	Hole (Ø)	A	L	
7X50	14	22	55	
7X70	14	22	75	
7X90	14	22	100	
7X140	14	22	145	

Saw Steel Plugs

Material: Steel

Surface treatment: Zinc Plated CR3+




SPECIFICATION				unit : mm	
Size	Drill (Ø)	Hole Depth	Screw Diam	L	
5X30	6	35	4-5	30	
6X32	8	37	5-6	32	
8X38	10	43	7-8	38	
8X60	10	65	7-8	60	
10X60	12	65	8-10	60	

Express Nails

Heat Treatment.

Material: Steel

Surface treatment: Zinc Plated CR3+




SPECIFICATION			unit : mm	
Size	Drill (Ø)	L	T	
6X30	6	30	0.8	
6X40	6	40	0.8	
6X50	6	50	0.8	
6X60	6	60	0.8	
6X80	6	80	0.8	
6X100	6	100	0.8	
8X70	8	70	1.0	
8X90	8	90	1.0	
8X110	8	110	1.0	
8X130	8	130	1.0	
8X150	8	150	1.0	
8X180	8	180	1.0	



Nylon Frame Anchors

Material: Plug - Nylon, Screw - Steel
Surface treatment: Screw - Zinc Plated CR3+





SPECIFICATION					unit : mm
Size	Drill (Ø)	Min Hole Depth	Min Depth in the Wall W	Max Fixing Length F	Screw
M8X100	8	60	46	44	5X110
M8X120	8	60	46	64	5X130
M8X140	8	60	46	84	5X150
M10X75	10	70	48	17	6X85
M10X100	10	70	48	42	6X110
M10X120	10	70	48	62	6X130
M10X140	10	70	50	80	6X150
M10X165	10	70	50	105	6X175



Nylon Hammer Fixings

Material: Plug - Nylon, Screw - Steel
Surface treatment: Screw - Zinc Plated CR3+




SPECIFICATION					unit : mm
Size	Drill (Ø)	Min Hole Depth	Min Depth in the Wall W	Max Fixing Length F	Screw
5X30	5	45	20	10	3.3X35
5X50	5	65	20	30	3.3X55
6X40	6	55	20	20	3.6X45
6X60	6	75	25	35	3.6X65
6X80	6	95	25	55	3.6X85
8X60	8	75	32	28	4.8X65
8X80	8	95	32	48	4.8X85
8X100	8	115	32	68	4.8X105
8X120	8	135	32	88	4.8X125
8X140	8	155	32	108	4.8X145



Nylon Fixings

Material: Plug - Nylon, Screw - Steel
Surface treatment: Screw - Zinc Plated CR3+




SPECIFICATION					unit : mm
Size	Drill (Ø)	Min Hole Depth	Min Depth in the Wall W	Max Fixing Length F	Screw
M6X60	6	75	20	10	4.0X65
M8X60	8	75	40	20	5.5X65
M8X80	8	95	40	40	5.5X85
M8X100	8	115	40	60	5.5X105
M8X120	8	135	40	80	5.5X125
M10X80	10	95	45	35	7X85
M10X100	10	115	45	55	7X105
M10X120	10	135	45	75	7X125
M10X140	10	155	45	95	7X145
M10X160	10	175	45	115	7X165



H.C. Bolt Anchors


Shield only
Material: Steel
Surface treatment: Zinc Plated CR3+

S TYPE




SPECIFICATION			unit : mm
Size	Length L	Hole (Ø) A	
M6	45	10	
M8	50	12	
M10	60	15	
M12	74	18	

R3 TYPE



SPECIFICATION			unit : mm
Size	Length L	Hole (Ø) A	
M6	45	12	
M8	50	14	
M10	60	16	
M12	75	20	

P TYPE



SPECIFICATION			unit : mm
Size	Length L	Hole (Ø) A	
M6	40	10	
M8	50	14	
M10	60	16	
M12	80	20	


H.C. BOLT APPLICATION

S, R3, P-Type With Hex Screw



SPECIFICATION		unit : mm
Size	Length L	
M6X55	55	
M8X65	65	
M10X75	75	
M12X90	90	

S, R3, P-Type With O, C-Hook



SPECIFICATION		unit : mm
Size	Length L	
M6X50	50	
M8X60	60	
M10X70	70	
M12X90	90	

R3, P-Type With Project Screw



SPECIFICATION		unit : mm
Size	Length L	
M6	69	
M8	74	
M10	90	
M12	105	




SPECIFICATION		unit : mm
Size	Length L	
M6	65	
M8	75	
M10	85	
M12	110	



Steel Hammer Anchors

Suspensions from concrete ceilings with slit-steel straps, punched band, nonius system hangers or wood battens.

Material: Steel
Surface treatment: Zinc Plated CR3+




SPECIFICATION			unit : mm
Size	Hole (Ø)	D	L
6X35	6	6	35
6X65	6	6	65




Key Anchors

Material: Steel
Surface treatment: Zinc Plated CR3+



Material: Steel
Surface treatment: Black Phosphorus



A TYPE

SPECIFICATION				unit : mm
Size	L	L1	L2	D
8X32	35	21	32	8.5

B TYPE


SPECIFICATION				unit : mm
Size	L	L1	L2	D
8X42	42	/	11	8.5



Toggle Bolts


Toggle Wing

Material: Steel
Surface treatment: Zinc Plated CR3+




Also can with Round head Screw,
O / C-HOOK, Washer

SPECIFICATION		SPECIFICATION	
B	L unit : mm	B	L unit : inch
M3	50 75	1/8"	2" 3"
M4	50 75	3/16"	2" 3"
M5	50 75	1/4"	2" 3"
M6	50 75	5/16"	2" 3"
M8	50 75	3/8"	2" 3"



Plastic Anchors

Material: PP



Item No.:	PAE	PAF	PAG
Grip range (mm)	4-12	15-19	24-28
Hole size (mm)	9-10	9-10	9-10




Item No.:	PAI	PAJ	PAK	PAL
Max. Fixture Thickness (With Screw Supplied)	9	25	25	38
Hole (mm)	8	8	8	8
Screw (mm)	3.5X30	5X50	5X50	5X36



Hammer Drive Anchors

Material: Sleeve - Zinc Alloy
Nail - Steel
Surface treatment: Nail-Zinc Plated CR3+




SPECIFICATION		unit : mm
Size	Hole (Ø)	
M5X22	5	
M6X20	6	
M6X30	6	
M6X40	6	
M6X50	6	
M6X65	6	

SPECIFICATION		unit : inch
Size	Hole (Ø)	
3/16"X7/8"	3/16"	
1/4"X3/4"	1/4"	
1/4"X1"	1/4"	
1/4"X1-1/4"	1/4"	
1/4"X1-1/2"	1/4"	
1/4"X2"	1/4"	
1/4"X2-1/2"	1/4"	
1/4"X3"	1/4"	




J-Nuts

Torque Strength: M4-min 2.0N.m, M5-min 3.0N.m, M6-min 4.5N.m.
Material: Steel
Surface treatment: Zinc Plated CR3+



Item No.:	SPECIFICATION					unit : mm
	Thread Size	A	B	C	D	
4SN	M4	8	11.9	1.8	16.5	
4LN	M4	8	11.9	1.8	21.4	
5SN	M5	9.7	13.5	1.8	18.2	
5LN	M5	9.7	13.5	1.8	22.5	
6SN	M6	11.1	15.9	1.8	18.6	
6LN	M6	11.1	15.9	1.8	23.3	

Item No.:	SPECIFICATION					unit : inch
	Thread Size	A	B	C	D	
4SN	6-32	0.315	0.469	0.07	0.65	
4LN	6-32	0.315	0.469	0.07	0.843	
5SN	10-24	0.382	0.532	0.07	0.717	
5LN	10-24	0.382	0.532	0.07	0.886	
6SN	1/4-20	0.437	0.626	0.07	0.732	
6LN	1/4-20	0.437	0.626	0.07	0.917	




Item No.:	SPECIFICATION					unit : mm
	Thread Size	A	B	C	D	
5SN	M5	9.7	11.9	2.0	13.2	
6SN	M6	11.1	13.8	2.0	18.6	



Steel Expansion Anchors

With Screw / Hook.
Material: Steel
Surface treatment: Zinc Plated CR3+




SPECIFICATION					unit : mm
Size	L	Drill (Ø)	Screw	Screw Length	Type
M4X39	35	8	M4	39	Pan Screw
M4X39	35	8	M4	39	Eye Hook
M4X39	35	8	M4	39	Open Hook
M4X39	35	8	M4	39	Short Hook
M4X39	35	8	M4	39	Medium Hook
M4X39	35	8	M4	39	Long Hook
M4X40	35	8	M4	40	Dual Screw-20
M4X40	35	8	M4	40	Dual Screw-35
M5X45	39	9	M5	45	Pan Screw
M5X45	39	9	M5	45	Eye Hook
M5X45	39	9	M5	45	Open Hook
M5X45	39	9	M5	45	Short Hook
M5X45	39	9	M5	45	Medium Hook
M5X45	39	9	M5	45	Long Hook
M5X45	39	9	M5	45	Dual Screw-20
M5X45	39	9	M5	45	Dual Screw-35



Nylon Expansion Anchors


With Screw / Hook.
Material: Plug - Nylon
Screw - Steel



SPECIFICATION					unit : mm
Size	L	Drill (Ø)	Screw	Screw Length	Type
M4X45	38	9	M4	45	Pan Screw
	38	9	M4	45	Eye Hook
	38	9	M4	45	Open Hook
	38	9	M4	45	Short Hook
	38	9	M4	45	Medium Hook
	38	9	M4	45	Long Hook
	38	9	M4	45	Dual Screw-20
	38	9	M4	45	Dual Screw-35
M5X50	45	12	M5	50	Pan Screw
	45	12	M5	50	Eye Hook
	45	12	M5	50	Open Hook
	45	12	M5	50	Short Hook
	45	12	M5	50	Medium Hook
	45	12	M5	50	Long Hook
	45	12	M5	50	Dual Screw-20
	45	12	M5	50	Dual Screw-35

Tie Wire Anchors


Material: Steel
Surface treatment: Zinc Plated CR3+



SPECIFICATION				unit : mm
Size	Eye Size d (Ø)	Wire Size	Drill (Ø)	Min Embedment
M6X60	6.3	6	6	35

Purlin Clips

Material: Steel
Surface treatment: Zinc Plated CR3+



SPECIFICATION			unit : mm
L	W	H	
43	19	1	

Hooks


Material: Steel
Surface treatment: Zinc Plated CR3+



C-Hook



L-Hook



O-Hook



AH-75



AH-79

Packing

Packaging can be customized.

BOX



PG-001

Window Box



PG-002

Plastic Box
With Euro Hole



PG-003

Plastic Box



PG-004

Plastic Box

BLISTER PACK



PG-005

Slide Blister



PG-006

Slide Blister



PG-007

Clamshell Blister



PG-008

Clamshell Blister

OTHERS



PG-009

Polybag With Header



PG-010

Blow Case



PG-011

Hardware Case



Packed on Wooden Pallet